

APPLICATION

FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, **Mel G. Wieting**, a citizen of the United States,
and **Terry M. Wieting**, a citizen of the United States, have invented a new and useful
grain bin monitoring system of which the following is a specification:

1
2
3 **Grain Bin Monitoring System**
4
5

6 **CROSS REFERENCE TO RELATED APPLICATIONS**

7 Not applicable to this application.
8
9

10 **STATEMENT REGARDING FEDERALLY**
11 **SPONSORED RESEARCH OR DEVELOPMENT**

12 Not applicable to this application.
13
14

15 **BACKGROUND OF THE INVENTION**
16
17
18

19 **Field of the Invention**
20

21 The present invention relates generally to grain bin monitors and more
22 specifically it relates to a grain bin monitoring system for efficiently monitoring
23 remote grain bins.
24
25

26 **Description of the Related Art**
27

28 Grain bins are utilized to store various types of grain such as wheat, corn and
29 soybeans. Grain bins may be comprised of various structures, shapes and materials

1 which is well known in the art. Grain bins have a storage reservoir that is capable of
2 storing and protecting a volume of grain. Aerator units are sometimes fluidly
3 connected to the grain bins to bring fresh air into the grain bin for drying the grain
4 when the humidity levels are too high to avoid spoilage.

5
6 Conventional methods of monitoring grain bins require the user to physically
7 visit each grain bin to measure the grain level, grain temperature and humidity within
8 the grain bin. Another problem with conventional methods of monitoring grain bins is
9 that they do not provide a convenient and easy to read chart/graph of the various grain
10 conditions for a user to view.

11
12 While these devices may be suitable for the particular purpose to which they
13 address, they are not as suitable for efficiently monitoring remote grain bins.
14 Conventional grain bins are difficult to monitor from a distance.

15
16 In these respects, the grain bin monitoring system according to the present
17 invention substantially departs from the conventional concepts and designs of the prior
18 art, and in so doing provides an apparatus primarily developed for the purpose of
19 efficiently monitoring remote grain bins.

1

2 **BRIEF SUMMARY OF THE INVENTION**

3

4 In view of the foregoing disadvantages inherent in the known types of grain bin
5 monitoring systems now present in the prior art, the present invention provides a new
6 grain bin monitoring system construction wherein the same can be utilized for
7 efficiently monitoring remote grain bins.

8

9 The general purpose of the present invention, which will be described
10 subsequently in greater detail, is to provide a new grain bin monitoring system that has
11 many of the advantages of the grain bin monitoring systems mentioned heretofore and
12 many novel features that result in a new grain bin monitoring system which is not
13 anticipated, rendered obvious, suggested, or even implied by any of the prior art grain
14 bin monitoring systems, either alone or in any combination thereof.

15

16 To attain this, the present invention generally comprises a main station, a
17 central unit in communication with the main station, a plurality of transmitter units in
18 communication with the central unit, and at least one sensor positionable within a
19 grain bin for determining condition data with respect to a grain bin. The sensor is in
20 communication with one of the transmitter units for providing the condition data to the
21 transmitter unit, wherein the transmitter unit automatically forwards the condition data
22 to a central unit that automatically forwards the condition data to the main station. In
23 the event of an alarm condition, an individual may be notified.

24

25 There has thus been outlined, rather broadly, the more important features of the
26 invention in order that the detailed description thereof may be better understood, and
27 in order that the present contribution to the art may be better appreciated. There are
28 additional features of the invention that will be described hereinafter and that will form
29 the subject matter of the claims appended hereto.

1
2 In this respect, before explaining at least one embodiment of the invention in
3 detail, it is to be understood that the invention is not limited in its application to the
4 details of construction and to the arrangements of the components set forth in the
5 following description or illustrated in the drawings. The invention is capable of other
6 embodiments and of being practiced and carried out in various ways. Also, it is to be
7 understood that the phraseology and terminology employed herein are for the purpose
8 of the description and should not be regarded as limiting.

9
10 A primary object of the present invention is to provide a grain bin monitoring
11 system that will overcome the shortcomings of the prior art devices.

12
13 A second object is to provide a grain bin monitoring system for efficiently
14 monitoring remote grain bins.

15
16 Another object is to provide a grain bin monitoring system that may be
17 monitored from a remote location.

18
19 An additional object is to provide a grain bin monitoring system that may be
20 utilized with various types of grain bins.

21
22 A further object is to provide a grain bin monitoring system that is capable of
23 monitoring various grain conditions.

24
25 Another object is to provide a grain bin monitoring system that can notify a
26 user of an alarm condition.

1 Other objects and advantages of the present invention will become obvious to the
2 reader and it is intended that these objects and advantages are within the scope of the
3 present invention.

4
5 To the accomplishment of the above and related objects, this invention may be
6 embodied in the form illustrated in the accompanying drawings, attention being called
7 to the fact, however, that the drawings are illustrative only, and that changes may be
8 made in the specific construction illustrated and described within the scope of the
9 appended claims.

1
2 **BRIEF DESCRIPTION OF THE DRAWINGS**
3

4 Various other objects, features and attendant advantages of the present
5 invention will become fully appreciated as the same becomes better understood when
6 considered in conjunction with the accompanying drawings, in which like reference
7 characters designate the same or similar parts throughout the several views, and
8 wherein:
9

10 FIG. 1 is diagram illustrating the overall communications of the present
11 invention with a single transmitter unit.
12

13 FIG. 2 is a diagram illustrating the overall communications of the present
14 invention with a plurality of transmitter units.
15

16 FIG. 3 is a block diagram illustrating the communications with the transmitter
17 unit.
18

19 FIG. 4 is a diagram illustrating the transmitter unit connected to the sensors.
20

21 FIG. 5 is a flowchart illustrating the overall functionality of the present
22 invention.
23

24 FIG. 6 is a flowchart illustrating the overall functionality of activating the
25 aerator unit.
26

DETAILED DESCRIPTION OF THE INVENTION

A. Overview

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, FIGS. 1 through 6 illustrate a grain bin monitoring system 10, which comprises a main station 20, a central unit 60 in communication with the main station 20, a plurality of transmitter units 50 in communication with the central unit 60, and at least one sensor positionable within a grain bin 12 for determining condition data with respect to a grain bin 12. The sensor is in communication with one of the transmitter units 50 for providing the condition data to the transmitter unit 50, wherein the transmitter unit 50 automatically forwards the condition data to a central unit 60 that automatically forwards the condition data to the main station 20. In the event of an alarm condition, an individual may be notified.

B. Main Station

The main station 20 receives the condition data from the transmitter units 50 as shown in Figure 1 of the drawings. The main station 20 may be comprised of any electronic device capable of receiving data communications via a signal or other communication means (e.g. computers 30, etc.). The main station 20 may be located in various remote locations near or far away from the grain bins 12 being monitored.

The main station 20 is preferably connected to a global computer 30 network (e.g. Internet 16). The main station 20 hosts and provides the condition data to one or more computers 30 via the Internet 16 in various forms such as but not limited to an HTML page. The main station 20 also preferably prepares charts and graphs which indicate grain level 14, temperature and humidity over a period of time for each grain bin 12 being monitored.

1
2 **C. Central Unit**

3 When more than one transmitter unit **50** is utilized, a central unit **60** is
4 preferably utilized to combine the condition data for each of the transmitter units **50**.
5 If only one transmitter unit **50** is utilized, the transmitter unit **50** may communicate
6 directly with the main station **20** without the usage of a central unit **60** as shown in
7 Figure 1 of the drawings.
8

9 The central unit **60** is in communication with the main station **20** as shown in
10 Figure 2 of the drawings. The central unit **60** is in communication with the main
11 station **20** via a signal (e.g. radio, wire, etc.). The central unit **60** may be comprised of
12 any computer **30** device capable of accumulating condition data from a plurality of
13 transmitter units **50** and sending the condition data for each grain bin **12** to the main
14 station **20** for additional data manipulation.
15

16 **D. Transmitter Units**

17 The plurality of transmitter units **50** in communication with the central unit **60**
18 as shown in Figure 2 of the drawings. If a single transmitter unit **50** is utilized, the
19 transmitter unit **50** may communicate directly with main station **20** as shown in Figure
20 1 of the drawings. The transmitter units **50** may communicate constantly or
21 periodically with the central unit **60** (or the main station **20**) via a conventional
22 communication system (e.g. radio, wire, etc.).
23

24 The transmitter units **50** may be comprised of any electronic device capable of
25 receiving and manipulating condition data received from the sensors. The transmitter
26 units **50** preferably send the condition data for each grain bin **12** to the central unit **60**
27 (or main station **20**) for additional data manipulation. The transmitter unit **50** is
28 preferably connected to a power source **52** such as batteries, direct power or solar
29 power as shown in Figure 3 of the drawings.

1
2 **E. Sensors**

3 At least one sensor **40, 41, 42, 44, 46** is positionable within or exterior of a
4 grain bin **12** for determining condition data with respect to a grain bin **12**. The
5 condition data may be comprised of interior temperature, grain temperature, exterior
6 temperature, humidity, grain level **14** and other conditions relating to a grain bin **12**
7 and grain.
8

9 The sensors **40, 41, 42, 44, 46** are in communication with the transmitter unit
10 **50** as shown in Figure 3 of the drawings. The transmitter unit **50** automatically
11 forwards the condition data to the central unit **60** (or main station **20**) that
12 automatically forwards the condition data to the main station **20**.
13

14 As shown in Figures 1, 3 and 4 of the drawings, the sensors **40, 41, 42, 44** may
15 be comprised of an interior temperature sensor that measures the interior temperature
16 of a grain bin **12** and the temperature of the grain at various levels, an exterior
17 temperature sensor for measuring the temperature exterior of a grain bin **12**, a level
18 sensor positionable within a grain bin **12** for measuring a grain level **14** within a grain
19 bin **12**, and a humidity sensor for measuring the humidity level within a grain bin **12**.
20 An exterior humidity sensor may also be utilized in communication with the
21 transmitter unit **50** to measure the humidity of the air external of the grain bin **12**.
22

23 The interior temperature sensor may be comprised of an elongate vertically
24 orientated structure as shown in Figure 4 of the drawings. The boxes within the
25 interior temperature sensor illustrate exemplary locations for each temperature sensor
26 for measuring the temperature of the grain at various pre-selected levels (e.g. every
27 foot or random levels). It can be appreciated that more than one transmitter unit **50**
28 and more than one sensor may be positioned within a grain bin **12**.
29

1 In addition, the transmitter unit **50** may be capable of communicating with an
2 aerator unit **18** for controlling an aerator unit **18** based upon the condition data. For
3 example, if the interior humidity exceeds a desired level and the exterior humidity is
4 below this level, the transmitter unit **50** may automatically activate the aerator unit **18**
5 to assist in lowering the interior humidity of the grain bin **12** as shown in Figure 6 of
6 the drawings. If the interior humidity falls below a desired level, the transmitter unit
7 **50** may automatically deactivate the aerator unit **18** as shown in Figure 6 of the
8 drawings. The same routine may be applied to the aerator unit **18** based upon the grain
9 temperature and the exterior temperature to maintain the grain at a desired level.

11 ***F. Alarm Condition Notification***

12 If an alarm condition exists (e.g. high humidity, high temperature, low grain
13 level **14**, etc.), the main station **20** preferably notifies a user of the condition. Various
14 means of automatically notifying the user such as but not limited to e-mail, instant
15 message, paging, phone call, facsimile or other communication means. More than one
16 means of communication may be utilized to notify the user of an alarm condition. It is
17 preferable to include information relating to the alarm condition.

19 ***G. Operation of Invention***

20 In operation, the grain bin **12** is monitored through the sensors **40, 41, 42, 44,**
21 **46.** The sensors **40, 41, 42, 44, 46** transmit the condition data (e.g. grain level **14,**
22 grain temperature, exterior temperature, interior humidity, exterior humidity, etc.) to
23 their respective transmitter units **50** as shown in Figure 3 of the drawings. The
24 transmitter units **50** then automatically or periodically transmit the condition data to
25 the central unit **60** as shown in Figure 2 of the drawings. The central unit **60** then
26 automatically or periodically transmits the combined condition data to the main station
27 **20.**

1 The main station **20** may be connected to the Internet **16** thereby allowing the
2 user to access the condition data via the Internet **16** through a webpage or similar data
3 transfer means. The condition data may then be viewed, printed or manipulated by the
4 user as desired to monitor the grain bins **12**.

5
6 If an alarm condition exists, the user is then notified through a desired
7 communication means of the alarm condition so the appropriate action may be taken.
8 In addition, if the temperature and/or humidity within the grain bin **12** exceeds a set
9 point, the aerator unit **18** for the individual grain bin **12** is automatically activated by
10 the corresponding transmitter unit **50** as shown in Figures 3 and 6 of the drawings.

11
12 As to a further discussion of the manner of usage and operation of the present
13 invention, the same should be apparent from the above description. Accordingly, no
14 further discussion relating to the manner of usage and operation will be provided.

15
16 With respect to the above description then, it is to be realized that the optimum
17 dimensional relationships for the parts of the invention, to include variations in size,
18 materials, shape, form, function and manner of operation, assembly and use, are
19 deemed to be within the expertise of those skilled in the art, and all equivalent
20 structural variations and relationships to those illustrated in the drawings and
21 described in the specification are intended to be encompassed by the present invention.

22
23 Therefore, the foregoing is considered as illustrative only of the principles of
24 the invention. Further, since numerous modifications and changes will readily occur to
25 those skilled in the art, it is not desired to limit the invention to the exact construction
26 and operation shown and described, and accordingly, all suitable modifications and
27 equivalents may be resorted to, falling within the scope of the invention.